

- Low running cost
- Complies with the Building Regulations (BRE Digest 398)
- Adaptable for different installations
- Can be wired for 2 speed operation
- Includes installation kit
- Easy to install
- Exceptionally quiet in operation
- 2 year guarantee



The DOMUS Multi Room Extract (MRE) system is a stylish and compact unit that provides a highly efficient and low cost form of continuous and controlled domestic ventilation from a single extraction unit. Its adaptability enables the system to be suitable for common house layouts and can be used in up to five rooms.

The MRE system prevents the need for multiple fans in different rooms and reduces, to one, the number of external outlets required.

A two speed* ball bearing motor is fitted to ensure long life and efficiency. The second speed acts as a powerful extraction boost which should be used when the removal of moisture and unwanted air is most needed e.g. after a bath or during cooking.

The 80mm inlets are for use in the bathroom or WC and the 125mm inlet should be used in the kitchen.

Fan spigots are fitted with flow regulators to balance the system. A simple to operate cursor device regulates the airflow in the kitchen.

The MRE system is normally installed in the loft or ceiling void and can be either fixed to a solid object (such as a joist or pillar) with a bracket, or it can be suspended with the cord provided in the kit.

Suspending the system

has the benefit of reducing unnecessary noise vibration.

Remember that extraction systems remove air from the building and in order to balance the airflow, provision must be made for replacement air.

**A single pole changeover switch is required.*





Product Code		Description	Extract performance			Power W	Weight kg	Electrical Specification
Boxed	Prepack		l/s	m³/hr	cfm			
MREK	n/a	Multi-Room Extractor Kit Two speed operation Low Speed High Speed	58 103	210 370	122 216	27 90	2.4	Electricity Supply 220 - 240V~50 Hz

The internal fan system of the unit is of the external rotor motor type designed for durability with low maintenance levels. The impeller generates high pressure levels to overcome duct resistance, but also minimises indoor sound levels to almost inaudible levels.



The system comes supplied as a kit with:

- 4 x 6m lengths of 80mm dia. PVC flexible hose
- 2 x 6m lengths of 125mm dia. PVC flexible hose
- 4 x 80mm dia. inlet (white)
- 1 x 125mm dia. inlet (white)
- Suspension cord
- Installation instructions

N.B. External outlet is not included. Please refer to the Ducting section (pages 9-13 for options).



5900 Gravity Flap Outlet



5902 Cowled Outlet



5904 Louvred Grille

The Domus MREK is only available for sale within the British Isles.

DIMENSIONS & PERFORMANCE GRAPH

